





GI Flush Box Series




1-GANG



2-GANG



3-GANG



4-GANG

1.0 mm STEEL

GALVANISED IRON FLUSH SWITCH & SOCKET BOXES

Manufacturer product family for recessed installation of switches, socket outlets and compatible wiring accessories.

Essential Construction Data

1.0 mm galvanised steel — Strong and corrosion resistant; standard zinc coating mass approx. 40 g/m².

47 mm depth — Generous wiring space.

20 mm / 25 mm knockouts — Flexible conduit entry.

M3.5 threaded lugs — Secure accessory fixing.

Earth terminal — Safe protective bonding.

1- to 4-gang range — Multiple installation options.

General Specifications


Parameter	Specification
Brand	FTM
Material	Galvanised sheet steel
Sheet thickness	1.0 mm
Zinc coating mass	Approx. 40 g/m ² (standard)
Box depth	47 mm
Knockouts	20 mm and 25 mm
Fixing lugs	M3.5 threaded; fixed and adjustable
Earthing	Integrated earth terminal
Mounting	Flush / recessed wall mounting
Applications	Masonry, brick and suitable dry walls
Compatibility	BS 4662 dimensional format

Dimensions & Configurations


Configuration	Nominal face size	Depth
1-Gang	75 × 75 mm	47 mm
2-Gang	135 × 75 mm	47 mm
3-Gang	205 × 75 mm	47 mm
4-Gang	275 × 75 mm	47 mm




1-Gang



2-Gang




3-Gang



4-Gang

Verified 1-Gang Dimensions



All dimensions nominal in mm. Confirmed depth: 47 mm.